



Dr. Kamiar Karimi Senior Technical Fellow Boeing Commercial Airplanes Mehdy Barekatein
Associate Technical Fellow
Boeing Commercial Airplanes

Jerry Hulm Associate Technical Fellow Boeing Commercial Airplanes

System Design Objectives

- Prevent failure but be capable of handling one if it occurs.
- Ensure that no single failure will endanger people or the airplane.



Continued Safe Flight and Landing Assured

Collaborating for Success

Collaboration with Tier 1 partner:

- Co-located during initial development efforts.
- Requirements and expectations were shared.
- Daily and weekly meetings were held at the working and/or management level.
- Monthly/quarterly meetings were held with senior leaders.

Collaboration with Tier 2 suppliers:

- Boeing was involved, reviewed selection and concurred.
- Boeing had regular direct involvement, including onsite visits.







Extensive Boeing Involvement

Battery System Design and Development

- Boeing and Thales jointly developed Specification Control Drawing (SCD) requirements.
- GS Yuasa, Securaplane and Thales designed and executed developmental tests.
- Design reviews were conducted with Boeing, GS Yuasa and Thales.
- Design reviews, prototype testing, analysis, lab events and Non-Advocate Reviews led to battery improvements.
- Boeing tested battery and charger prototypes to ensure they met airplane system and safety requirements.

Regular Interaction, Close Contact During Development

Design Evolution: Designing for Safety

Design evolves with testing.

- This iterative process ensures continued improvement.
- Modifications were fully tested to validate performance.

Design evolution was coordinated between all parties.

- Boeing updated formal requirements.
- Boeing, Thales and GS Yuasa conducted developmental testing.
- Boeing kept the FAA informed of changes and the rationale for them.



Summary


- Boeing was fully involved with its suppliers in battery system design development.
- The battery system design evolved over time as a result of testing and multiple design reviews.
- The certification process verified that the design complied with all Boeing and regulatory requirements.

Design Evolution Reflects Our Safety Commitment



Backup

787 Battery Design Timeline



Why Lithium Ion?

- Requirements included:
 - Safety.
 - Power capability.
 - Charging characteristics.
 - Storage capacity.
 - Low weight.
- Technologies evaluated:
 - Nickel cadmium.
 - Lithium cobalt.
 - Lithium manganese.





777

Feature	Lithium Ion (Lithium Cobalt)	Nickel Cadmium
Voltage	32V	24V
Maximum weight	63 lb	107 lb
Current provided for power-up	150 amps	16 amps

Lithium Ion Best Suited for 787 Requirements

Special Condition and Issue Paper

- The FAA applied the Special Condition to models built by several manufacturers.
- The FAA sent Issue Paper SE-9 to Boeing in June 2005.
- Boeing responded to the issue paper in December 2005.
 - Boeing agreed with the FAA's draft Special Condition and proposed how compliance would be shown.
 - The FAA modified one requirement, regarding flight crew indication of battery capacity, based on Boeing's input.

Tests Conducted (1 of 2)

Test Content	Test Article	Test Name	Eng	Cert
		High Temperature	✓	
		Low Temperature	✓	
	Cell	Altitude	✓	
	Cell	Overpressure	✓	
		Temperature Variation	✓	
		Decompression	✓	
Climatic		High Temperature		✓
Climatic		Low Temperature		✓
Batte		Altitude		✓
	Dattam	Overpressure		✓
	Battery	Humidity	✓	✓
		Temperature Variation		✓
		Decompression		✓
		Fluid Susceptibility	✓	
	Cell	Acceleration	✓	
		Random Vibration	✓	✓
		Fan Blade Loss / Windmilling Vibration	✓	✓
Dankaniaal		High Power Vibration	✓	✓
Mechanical	Battery	Bench Handling Shock	✓	✓
		Shipping Container Shock	✓	✓
		Acceleration		✓
		Electrolyte Leakage		✓

Tests Conducted (2 of 2)

Test Content	Test Article	Test Name	Eng	Cert
Electromagnetic Interference	Battery	AF Capacitive Coupling		✓
		AF Inductive Coupling		✓
		RF Conducted Emissions		✓
		RF Radiated Emissions		✓
		AF Electric Field Susceptibility		✓
		AF Magnetic Field Susceptibility		✓
		Conducted RF Susceptibility		✓
		Radiated RF Susceptibility		✓
		Induced Spike Susceptibility		✓
		Ground-injected Transient Susceptibility		✓
		Cable-injected Transient Susceptibility		✓
		Lightning Induced Multiple-Burst Transient		
		Susceptibility		√
		Electrostatic Discharge Susceptibility		√
		BMU Function Test		✓
	Cell	Endurance	✓	
	Battery	Endurance	✓	
Other Tests		UN Transportation Tests	✓	
		Charge/Discharge Performance	✓	
	Battery and Charger	Battery / BCU Integration Tests	✓	

Abuse Tests Conducted

Test Content	Test Article	Test Name	Eng	Cert
Abuse Tests	Cell	Nail Penetration	✓	
		External Short Circuit	✓	
		Overheat	✓	
		Crush/Impact	✓	✓
		Step Overcharge Destructive	✓	
		Constant Current Overcharge Destructive	√	
	Battery	High Rate Charging	✓	
		Nail Penetration	✓	
		Flame Test	✓	
		High Temperature Storage		✓
		Low Impedance External Short Circuit	✓	✓
		High Impedance External Short Circuit		✓
		Overcharge to 36V	✓	✓
		Over discharge		✓
	Battery and Charger	External Short Circuit	✓	